LISTING OF CLAIMS

Claims 1-10 (cancelled)

Claim 11 (currently amended) - A <u>vehicle</u> lifting jack accessory <u>which</u> includes an elongate standard comprising, in combination:

a sleeve <u>having no interior obstructions and dimensioned to overlie</u>

<u>the standard</u> having first and second <u>open</u> ends <u>to receive the standard</u>

<u>therethrough</u> and an adjunct projecting from a side of said sleeve including means

for engaging other objects therewith.

Claim 12 (previously presented) - The accessory of claim 11 wherein said adjunct includes a clevis hole for receiving shackle rigging.

Claim 13 (previously presented) - The accessory of claim 11 wherein said adjunct includes a chain lock means.

Claim 14 (previously presented) - The accessory of claim 13 wherein said chain lock means includes a rectangular hollow passing through a wall of said adjunct in communication with a chain slot portion dimensioned to receive one chain's thickness therein defining said chain lock.

Claim 15 (previously presented) - The accessory of claim 12 including a nose on said adjunct on one end thereof.

Claim 16 (previously presented) - The accessory of claim 15 including a spike on said adjunct at a remote end thereof.

Claim 17 (previously presented) - The accessory of claim 11 including a plurality of teeth on one surface of said adjunct.

Claim 18 (previously presented) - A lifting jack accessory in which the lifting jack includes an elongate, perforated standard, a ratcheting mechanism overlying the standard, the ratcheting mechanism including a load engaging nose operatively coupled to a ratcheting handle, said accessory comprising, in combination:

a sleeve dimensioned to slideably overlie the standard and translate along a length of the standard,

means for allowing axial translation of said sleeve along said standard and for fixing said sleeve on said standard,

a purchase area at a first end of said sleeve, and a plurality of spikes at a second end of said sleeve.